
















| C/N | 针板 | | 主传送齿 | | 副传送齿 | | 压脚(组件) | | 注释 |
|-----|------|-------------|-------------|---|--------------|---|-------------|---|------------------------|
| | 品号 | 形状 | 品号 | 形状 | 品号 | 形状 | 品号 | 形状 | |
| 1 | 2201 | D1109436D00 | B1613430A00 |  | B1613432A00A |  | B15244300BA |  | 标准发货用标准针位组合 |
| 2 | 2202 | D1109436D00 | B1613430A00 |  | B1613432A00A |  | B15244320BA |  | 压脚 化纤拉伸缝制用、对应起皱 |
| 3 | 2203 | D1109436D00 | B1613430A00 |  | B1613432A00A |  | B15244310BA |  | 压脚 收缩缝制用 (有布料避让) |
| 4 | 2204 | D1109436D00 | B1613436000 |  | B1613432A00A |  | B15244310BA |  | 压脚 收缩缝制用 (副传送齿 逆齿) |
| 5 | 2205 | D1109436D00 | B1613430A00 |  | B1613430B00A |  | B15244300BA |  | 拉伸缝纫传送效果好的组合、(副传送齿 逆齿) |

| C/N | 针板 | | 主传送齿 | | 副传送齿 | | 压脚(组件) | | 注释 |
|-----|------|-------------|-------------|----|--------------|----|-------------|----|-----------------------------|
| | 品号 | 形状 | 品号 | 形状 | 品号 | 形状 | 品号 | 形状 | |
| 6 | 2206 | D1109436D00 | B1613430A00 | | B1613430B00A | | B15244320BA | | 拉伸缝切传送效果好的组合、对应起皱 (副传送齿 逆齿) |
| 7 | 2207 | D1109436D00 | B1613432G0B | | B1613432G0A | | B15244300BA | | 厚料用传送齿的组合 |
| 8 | 2208 | D1109436D00 | B1613432G0C | | B1613432G0A | | B15244310BA | | 厚料用 收缩缝切传送效果好的组合 (主传送 逆齿) |
| 9 | 2209 | D1109436D0A | B1613430A00 | | B1613432A00A | | B15244300BA | | 薄料用 拉伸缝切用 |
| 10 | 2210 | D1109436D0A | B1613430A00 | | B1613432A00A | | B15244320BA | | 薄料用 拉伸缝切用、对应起皱 |

| C/N | 针板 | | 主传送齿 | | 副传送齿 | | 压脚(组件) | | 注释 |
|-----|------|-------------|-------------|----|--------------|----|-------------|----|----------------------|
| | 品号 | 形状 | 品号 | 形状 | 品号 | 形状 | 品号 | 形状 | |
| 11 | 2211 | D1109436D0A | B1613430A00 | | B1613432A00A | | B15244310BA | | 薄料用 拉伸缝勿用、对应起皱 |
| 12 | 2212 | D1109436D0A | B1613430A00 | | B1613430B00A | | B15244320BA | | 极薄料 有防止起皱效果(副传送齿 逆齿) |
| 13 | 2213 | D1109436D00 | B1613432C00 | | B1613432D00A | | B15240120BA | | 差速比1:1 请在P=2mm以下使用 |
| 14 | 2214 | D1109436D00 | B1613432E00 | | - | - | B15240120BA | | 无差速使用, 可使用普通平缝的压脚 |
| 15 | 2215 | D1109436D00 | B1613430C00 | | - | - | B15240120BA | | 无差速使用, 可使用普通平缝的压脚 |