























































C/N	定规		传送齿		压脚(组件)		切刀		注释
	品号	形状	品号	形状	品号	形状	品号	形状	
1	2501 B1190522Y0A		B1613522N00A		B1524522NB0A		B4145530C00		后切刀型
2	2502 B1190522X00		B1613522N00A		B1524522NB0A		B4121522000		
3	2503 B1190522X0B		B1613522N0C		B1524522NB0A		B4121522000		对B1190522X00, 将送布槽由2→改为3
4	2504 B1190522S00		B1613522N00A		B1524522NB0A		B4121522000		D型规格的出厂标准规格针位在DLM-5200NH附属品包装内
5	2505 B1190522Y00		B1613522N00A		B1524522NB0A		B4121522000		

C/N	定规		传送齿		压脚(组件)		切刀		注释
	品号	形状	品号	形状	品号	形状	品号	形状	
6	2506	11362753	-	-	B1524522NB0A		B4121522000		模板机用
7	2507	B1190522Y0R	B1613522N0D		B1524522NB0A		B4121522000		对B1190522Y00, 将送布槽由2➡改为3
8	2508	B1190522T00	B1613522N00A		B1524522NB0A		B4121522000		F型规格的出厂标准规格针位
9	2509	B1190522T0A	B1613522N00A		B1524522NB0A		B4121522A00		前切刀型, 对B1190522T00, 落针前一直可下刀
10	2510	B1190522Y0C	B1613522N00A		B1524522NB0A		B4121522000		对B1190522T00将针孔直径变为φ1.9→1.2mm

C/N	定规		传送齿		压脚(组件)		切刀		注释
	品号	形状	品号	形状	品号	形状	品号	形状	
11	2511	B1190522T0D 	B1613522N0D 	B1524522NB0A 	B4121522000 	对B1190522T00, 将送布槽由2→改为3			
12	2512	B1190522Y0F 	B1613522N00A 	B1524522NB0A 	B4121522000 				
13	2513	B1190522U00 	B1613522W00A 	B1524522AB0 	B4121522000 	H型规格的出厂标准针位			
14	2514	B1190522U0A 	B1613522A0AA 	B1524522AB0 	B4121522000 	4齿防堵布用			
15	2515	B1190522Y0B 	B1613522W00A 	B1524522AB0 	B4121522000 				

C/N	定 规		传送齿		压脚(组件)		切 刀		注 释
	品 号	形 状	品 号	形 状	品 号	形 状	品 号	形 状	
16	2516	B1190522V00	B1613522W00A	B1524522AB0	B4121522000				
17	2517	B1190522V0A	B1613522B00	B1524522AB0	B4121522000			针对B1190522V00缩短了送布槽的长度	
18	2518	B1190522Y0M	B1613522W00A	B1524522AB0	B4121522000				