










































































































C/N	压脚(组件)				上送料压脚				针板		传送齿		注释
	品号	形状	品号	形状	品号	形状	品号	形状					
1	2301	B1524491AB0			B3026490A00		B1109490E00	 φ1.9mm	B1613490E00	 P = 1.5mm	围裙、枕头等加褶边用，在压脚上安装向导带加3个褶子的类型。		
2	2302	B1524491BB0			B3026490B00		B1109450A0B	 φ1.4mm	B1613450A00	 P = 1.15mm	用于缝制女服、罩衫的抵肩、接袖口等褶皱用		
3	2303	B1524491BB0			B3026490B00		B1109450B0B	 φ1.9mm	B1613450A00	 P = 1.15mm	标准规格。 用于防止中厚材料缝口不齐、收口缝齐用。		
4	2304	40133520			40133637		B1109450B0B	 φ1.9mm	40133638	 P = 1.15mm	新加坡规格。用于防止中厚材料缝口不齐、收口缝齐用。		
5	2305	B1524491BB0			B3026490B00		B1109450C0B	 3 × 1.6mm	B1613450A00	 P = 1.15mm	防止厚物外套材料等的缝口不齐，收口缝齐用。		
6	2306	B1524491BB0			B3026490B0D		B1109450A0B	 φ1.4mm	B1613450A00	 P = 1.15mm	用于防止绗缝布料、尼龙、塔夫他毛绒、衬里、妇女薄物材料等发生布疵用 上传送的是马拉坦橡胶		





















C/N	压脚(组件)		上送料压脚		针板		传送齿	注释				
	品号	形状	品号	形状	品号	形状	品号					
7	2307	B1524491BB0			B3026490B0D		 φ1.9mm	B1613450A00	 P = 1.15mm	用于防止绗缝布料、尼龙、塔夫他毛绒、衬里、妇女薄物材料等发生布疵用上传送的是乌拉坦橡胶		
8	2308	B1524491BB0			B3026490B0D		 3 × 1.6mm	B1109450C0B	 P = 1.15mm	B1613450A00	 P = 1.15mm	用于防止绗缝布料、尼龙、塔夫他毛绒、衬里、妇女薄物材料等发生布疵用上传送的是乌拉坦橡胶
9	2309	B1524491BBE		-	-	-	 φ1.9mm	B1109450B0B	 φ1.9mm	B1613450A00	 P = 1.15mm	作为普通平缝使用时的压脚
10	2310	B1524491EB0			B3026490B0G		 φ1.9mm	B1109490E00	 φ1.9mm	B1613490E00	 P = 1.5mm	用于防止绗缝布料、尼龙、塔夫他毛绒、衬里、妇女薄物材料等发生布疵用上传送的是乌拉坦橡胶
11	2311	B1524491BBJ			B3026490B0J		 φ1.6mm	B1109450G0B	 φ1.6mm	B1613450G00	 P = 1.15mm	用于缝制女服、罩衫的抵肩、接袖口等褶皱用罩衫加花边等细布（1~2mm）的褶裥缝
12	2312	B1524491BB0			B3026490B0K		 φ1.9mm	B1109490E00	 φ1.9mm	B1613490B0K	 P=1.0mm	用于防止绗缝布料、尼龙、塔夫他毛绒、衬里、妇女薄物材料等发生布疵用可打褶裥的类型













C/N	压脚(组件)		上送料压脚		针板		传送齿		注释
	品号	形状	品号	形状	品号	形状	品号		
13	2313	B1524491BB0			B3026490B0M		 $\phi 1.4\text{mm}$	B1613450A00 $P = 1.15\text{mm}$ 	B3026490B00(上传送压脚) 的齿加大 ($P=1.5\text{mm}$) 传力加强的类型
14	2314	B1524491BB0			B3026490B0M		 $\phi 1.9\text{mm}$	B1613450A00 $P = 1.15\text{mm}$ 	B3026490B00(上传送压脚) 的齿加大 ($P=1.5\text{mm}$) 传力加强的类型
15	2315	B1524491BB0			B3026490B0M		 $3 \times 1.6\text{mm}$	B1613450A00 $P = 1.15\text{mm}$ 	B3026490B00(上传送压脚) 的齿加大 ($P=1.5\text{mm}$) 传力加强的类型
16	2316	B1524491BB0			B3026490B0D		 $\phi 1.4\text{mm}$	B1613490B0V $P = 1.15\text{mm}$ 	操作员一侧的齿尚未加工的细宽度传送齿。 对打褶裥、皱褶效果好、乌拉坦上传齿
17	2317	B1524491BB0			B3026490B0D		 $\phi 1.9\text{mm}$	B1613490B0V $P = 1.15\text{mm}$ 	操作员一侧的齿尚未加工的细宽度传送齿。 对打褶裥、皱褶效果好、乌拉坦上传齿
18	2318	B1524491BB0			B3026490B0D		 $3 \times 1.6\text{mm}$	B1613490B0V $P = 1.15\text{mm}$ 	操作员一侧的齿尚未加工的细宽度传送齿。 对打褶裥、皱褶效果好、乌拉坦上传齿






















C/N	压脚(组件)		上送料压脚		针板		传送齿	注释
	品号	形状	品号	形状	品号	形状	品号	
19	2319	B1524491BBW			B1109450A0B		B1613450A00	
								适用于做褶裥的类型
20	2320	B1524491BBW			B1109450B0B		B1613450A00	
								适用于做褶裥的类型
21	2321	B1524491BBW			B1109450C0B		B1613450A00	
								适用于做褶裥的类型
22	2322	B1524491BB0			B1109450A0B		B1613450A00	
								加大B3026490B00的接触面、加强传送力的类型
23	2323	B1524491BB0			B1109450B0B		B1613450A00	
								加大B3026490B00的接触面、加强传送力的类型
24	2324	B1524491BB0			B1109450C0B		B1613450A00	
								加大B3026490B00的接触面、加强传送力的类型




















C/N	压脚(组件)				上送料压脚		针板		传送齿		注释
	品号	形状		品号	形状	品号	形状	品号			
25	2325	B1524491BBJ			B3026490B0Y		B1109450G0B	 φ1.6mm	B1613450G00	 P=1.15mm	将B3026490B0J的齿3列排列，防止布滑脱
26	2326	B1524491CB0			B3026490C00		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	白衬衫、罩衫、女服、上衣等各种隐藏针脚缝法用 (针脚宽度1mm右段压脚)
27	2327	B1524491CBA			B3026490C00		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	白衬衫、罩衫、女服、上衣等各种隐藏针脚缝法用 (针脚宽度2mm右段压脚)
28	2328	B1524491CBB			B3026490C00		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	白衬衫、罩衫、女服、上衣等各种隐藏针脚缝法用 (针脚宽度3mm右段压脚)
29	2329	B1524491CBC			B3026490C00		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	白衬衫、罩衫、女服、上衣等各种隐藏针脚缝法用 (针脚宽度5mm右段压脚)
30	2330	B1524491CBD			B3026490C00		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	白衬衫、罩衫、女服、上衣等各种隐藏针脚缝法用 (针脚宽度1mm左段压脚)





















C/N	压脚(组件)		上送料压脚		针板		传送齿	注释
	品号	形状	品号	形状	品号	形状	品号	
31	2331	B1524491DB0	B3026490D00	B1109490C0E	B1613490C0E	$P=1.5\text{mm}$	厚料素材的各种暗缝针脚用。(增加针板厚度的类型) 可与C型整体的压脚组合	
32	2332	B1524491CBF	B3026490D0K	B1109490D00	B1613490D00	$P=1.5\text{mm}$	白衬衫、罩衫、女服、上衣等各种贴隐藏针脚缝法用 (针脚宽度0.8mm左段压缝)	
33	2333	B1524491CBG	B3026490D00	B1109490D00	B1613490D00	$P=1.5\text{mm}$	B1524490DA0前后的R加高, 防止布被挂住的类型	
34	2334	B1524491CBH	B3026490D00	B1109490D00	B1613490D00	$P=1.5\text{mm}$	两侧附有缝合引导的类型。(左右针脚宽度均1.5mm)	
35	2335	B1524491CBJ	B3026490D00	B1109490D00	B1613490D00	$P=1.5\text{mm}$	B1524491DA0的落针部由槽→变更为圆孔 使之压脚(下)底面的管道槽能加工, 使管道夹具靠近落针附近。	
36	2336	B1524491CBK	B3026490D00	B1109490D00	B1613490D00	$P=1.5\text{mm}$	白衬衫、罩衫、女服、上衣等各种针脚缝用 (针脚宽度7mm左段压缝)	





















C/N	压脚(组件)				针板				传送齿	注释	
	品号	形状	品号	形状	品号	形状	品号	P = 1.5mm			
37	2337	B1524491CBL			B3026490C0L		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	用于缝制裙子腰带的落疏缝用 附带导缝板、从表面侧落下的类型（台阶压脚）
38	2338	B1524491CBM		 9mm	B3026490D00		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	白衬衫、罩衫、女服、上衣等各种针脚缝用 （针脚宽度9mm右段压缝）
39	2339	B1524491CBN		 6mm	B3026490D00		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	白衬衫、罩衫、女服、上衣等各种针脚缝用 （针脚宽度6mm左段压缝）
40	2340	B1524491CBQ		 1mm	B3026490C0Q		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	将上传送的接触面加宽的类型 （针脚宽度1mm左段压脚）
41	2341	B1524491CBT			B3026490C0T		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	CL类型的细宽类型、带子一侧由上传送压脚传送的类型（台阶压脚）
42	2342	B1524491CBW		 4mm	B3026490D00		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	B1524491DA0带有缝合导向部的类型（针脚宽度4mm）






















C/N	压脚(组件)		上送料压脚		针板		传送齿		注释
	品号	形状	品号	形状	品号	形状	品号	P=1.5mm	
43	2343	B1524491CBX		B3026490D00		B1109490D00		B1613490D00	白衬衫、罩衫、女服、上衣等各种针脚缝用 (针脚宽度6mm右段压缝)
44	2344	B1524491CBY		B3026490C00		B1109490D00		B1613490D00	使得布料容易旋转的类型。(针脚宽度1mm右段压脚)
45	2345	B1524491DB0		B3026490D00		B1109490D00		B1613490D00	白衬衫、罩衫等的小回转用
46	2346	B1524491DBA		B3026490D00		B1109490D00		B1613490D00	裙子、宽松裤子的皮带缝合等各种针脚用(针脚宽度2mm)
47	2347	B1524491DBB		B3026490D00		B1109490D00		B1613490D00	裙子、宽松裤子的皮带缝合等各种针脚用(针脚宽度5mm)
48	2348	B1524491DBC		B3026490D0C		B1109490D00		B1613490D00	白衬衫、罩衫、女服等各种边缘缝合用 (针脚宽度1mm右段压脚)













C/N	压脚(组件)		上送料压脚		针板		传送齿		注释	
	品号	形状	品号	形状	品号	形状	品号	P=1.5mm		
49	2349	B1524491DBD	 	B3026490D0D		B1109490D00		B1613490D00		白衬衫、罩衫、女服等各种边缘缝合用 (针脚宽度2mm右段压脚)
50	2350	B1524491DBE	 	B3026490D00		B1109490D00		B1613490D00		白衬衫、罩衫、女服等各种边缘缝合用 (针脚宽度3mm右段压脚)
51	2351	B1524491DBF	 	B3026490D00		B1109490D00		B1613490D00		白衬衫、罩衫、女服等各种边缘缝合用 (针脚宽度4mm右段压脚)
52	2352	B1524491DBG	 	B3026490D00		B1109490D00		B1613490D00		白衬衫、罩衫、女服等各种边缘缝合用 (针脚宽度5mm右段压脚)
53	2353	B1524491DBJ	 	B3026490D00		B1109490D00		B1613490D00		裙子、长裤等各种针脚缝合用。(带缝合引导弹簧3mm)
54	2354	B1524491DBK	 	B3026490D0K		B1109490D00		B1613490D00		衬衫、罩衫、女服、上衣等的隐藏针脚缝法用 (针脚宽度1mm左段压脚)






















C/N	压脚(组件)			上送料压脚		针板		传送齿		注释
	品号	形状		品号	形状	品号	形状	品号	P=1.5mm	
55	2355	B1524491DBL	 	B3026490D00		B1109490D00		B1613490D00		白衬衫、罩衫、女服、上衣等各种针脚缝用 (针脚宽度7mm右段压脚)
56	2356	B1524491DBM	 	B3026490D00		B1109490D00		B1613490D00		白衬衫、罩衫、女服、上衣等各种针脚缝用 (针脚宽度3mm左段压脚)
57	2357	B1524491DBN	 	B3026490D0N		B1109490D00		B1613490D00		衬衫、罩衫、女服、上衣等的隐藏针脚缝法用 (针脚宽度2mm左段压脚)
58	2358	B1524491DBP	 	B3026490D00		B1109490D00		B1613490D00		衬衫、罩衫、女服、上衣等的隐藏针脚缝法用 (带缝合引导弹簧1.5mm)
59	2359	B1524491DBR	 	B3026490D0R		B1109490D00		B1613490D00		用于缝制女服、罩衫、连衣裙、外套、运动上衣等的滚边。
60	2360	B1524491DBT	 	B3026490D0T		B1109490D00		B1613490D00		为B3026490D00的宽度1/2的类型 (针脚宽度1mm右段压脚)




















C/N	压脚(组件)			上送料压脚		针板		传送齿		注释	
	品号	形状		品号	形状	品号	形状	品号	P=1.5mm		
61	2361	B1524491DBV			B3026490D00		B1109490D00		B1613490D00		DA类型的反类型。(带针脚导向弹簧2mm)
62	2362	B1524491DBW			B3026490D0W		B1109490D00		B1613490D00		衬衫、罩衫、女服、上衣等的隐藏针脚缝法用 (针脚宽度1.5mm右段压脚)
63	2363	B1524491DBZ			B3026490C00		B1109490D00		B1613490D00		将敞领半袖衬衫的暗缝用B1524491BA0长度26mm→33mm
64	2364	B1524491EB0			B3026490B00		B1109490E00		B1613490E00		对有伸缩性的素材有效果的类型
65	2365	B1524491EB0			B3026490B00		B1109490E0D		B1613490E00		对有伸缩性的素材有效果的类型
66	2366	B1524491EB0			B3026490B00		B1109490E00		B1613490E0A		防止褶料、尼龙、塔夫绸、衬里等薄物材料造成布疵用 B1613490E00格上了乌拉坦的类型


























C/N	压脚(组件)		上送料压脚		针板		传送齿	注释	
	品号	形状	品号	形状	品号	形状	品号		
67	2367	B1524491EB0			B3026490B00				操作人员一侧的未加工的宽度大的传送齿和减小针孔直径的针板、对打褶裥和皱褶有效
68	2368	B1524491EB0			B3026490B00				E类型的改良型。(防止布料滑脱) 传送齿：4颗齿→3颗斜齿
69	2369	B1524491FB0			B3026490F00				白衬衫、罩衫等各种针脚缝合用（针脚宽度5mm~12mm） ※针脚引导B1540490FA0
70	2370	B1524491FBA			B3026490F00				白衬衫、罩衫等各种针脚缝合用（针脚宽度6mm~12mm） ※针脚引导B1540490FA0
71	2371	B1524491FBB			B3026490F00				白衬衫、罩衫等各种针脚缝合用（针脚宽度7mm~12mm） ※针脚引导B1540490FA0
72	2372	B1524491FBD			B3026490F0D				FA类型的反类型（针脚宽度6~13mm） ※针脚引导B1540490FA0























C/N	压脚(组件)		上送料压脚		针板		传送齿	注释	
	品号	形状	品号	形状	品号	形状	品号		
73	2373	B1524491FBE			B3026490F0E		B1109490F00  φ1.6mm	B1613490F00  P = 1.15mm	对白衬衫、罩衫等各种针脚缝，传送间距不均匀有效果的类型 (针脚宽度6~12mm) ※针脚引导B1540490FA0
74	2374	B1524491FB0			B3026490F0J		B1109490F00  φ1.6mm	B1613490F00  P = 1.15mm	用于防止被褥材料、尼龙、塔夫绸、衬里等薄物材料等的布疵 B3026490F00 (上送料压脚) 烙上乌拉坦的类型 (针脚宽度5~12mm) ※针脚引导B1540490FA0
75	2375	B1524491FBL			B3026491F0L		B1109450J00A  φ1.9mm	B1613490J00  P=1.5mm	前胸拉链装饰缝制用。(针脚宽度2~9.5mm右用) ※针脚引导B1540490FA0
76	2376	B1524491GBA			B3026491G0A		B1109450G0B  φ1.6mm	B1613450G00  P = 1.15mm	M类型的反类型 (针脚宽度1mm右段压脚)
77	2377	B1524491GBB			B3026491G0B		B1109450G0B  φ1.6mm	B1613450G00  P = 1.15mm	白衬衫、罩衫等各种缝合用 (针脚宽度1.3mm)
78	2378	B1524491HB0			B3026490H00		B1109490S00  φ1.4mm	B1613490S00A  P = 1.15mm	仿鹿皮、人造皮革等不易传送的材料用 HA类型的压脚上附有特氟隆的类型。






















C/N	压脚(组件)		上送料压脚		针板		传送齿	注释
	品号	形状	品号	形状	品号	形状	品号 P = 1.5mm	
79	2379	B1524491HBA			B1109490S00		B1613490S00A	
						 φ1.4mm	 P = 1.15mm	仿鹿皮、人造皮革等不易传送的材料用 因为按住布料较实，稳定褶皱效果好。
80	2380	B1524491JB0			B1109450J00A		B1613450J00A	
						 φ1.9mm	 P=1.15mm	缝制连衣裙、女服、裙子、宽松长裤、工作服上衣等拉链附着用
81	2381	B1524491JBA			B1109450J00A		B1613450J00A	
						 φ1.9mm	 P=1.15mm	缝制连衣裙、女服、裙子、宽松长裤、工作服上衣等拉链附着用
82	2382	B1524491JBB			B1109450J00A		B1613450J00A	
						 φ1.9mm	 P=1.15mm	缝制连衣裙、女服、裙子、宽松长裤、工作服上衣等拉链附着用
83	2383	B1524491JBC			B1109450J00A		B1613450J00A	
						 φ1.9mm	 P=1.15mm	对连衣裙，女服，裙子，运动服装等带拉链，防止扭拧效果好。
84	2384	B1524491JBF			B1109450J00A		B1613450J00A	
						 φ1.9mm	 P=1.15mm	对连衣裙，女服，裙子，运动服装等带拉链， 对布料覆盖在拉链上时有效果













C/N	压脚(组件)			上送料压脚		针板		传送齿		注释	
	品号	形状		品号	形状	品号	形状	品号	P=1.5mm		
85	2385	B1524491JBG			B3026490J0G		B1109490D00	 φ1.6mm	B1613490D00	 P=1.5mm	用于裙子等缝制暗拉链用
86	2386	B1524491JB0		 3°	B3026491J00		B1109450J00A	 φ1.9mm	B1613490J00	 P=1.5mm	加大间距、增强传送力的传送齿
87	2387	B1524491JBK			B3026490J0K		B1109490P00	 φ1.9mm	B1613490P00	 P=1.15mm	与JB类型相反。落针右侧压脚
88	2388	B1524491JBL			B3026490J0K		B1109490P00	 φ1.9mm	B1613490P00	 P=1.15mm	JK类型压脚的落针部避让形状的改变型
89	2389	B1524491JBM			B3026490J0B		B1109450J00A	 φ1.9mm	B1613450J00A	 P=1.15mm	对连衣裙、女服、裙子、运动服装等带拉链
90	2390	B1524491JBN			B3026491J0N		B1109450J00A	 φ1.9mm	B1613450J00A	 P=1.15mm	对连衣裙、女服、裙子、运动服装等带拉链，抑制布不稳的类型。

C/N	压脚(组件)				上送料压脚		针板		传送齿	注释
	品号	形状		品号	形状	品号	形状	品号	P=1.5mm	
91	2391	B1524491JBC			B3026490JOP		B1109450J00A  φ1.9mm	B1613450J00A  P=1.15mm	用于防止被褥织物材料、尼龙、塔夫绸、衬里等薄物材料等的布疵 B3029490J0C烙上马拉坦的类型	
92	2392	B1524491KBE			B3026490C00		B1109490D00  φ1.6mm	B1613490D00  P=1.5mm	1.5mm缝合用左段压脚	
93	2393	B1524491LB0			B3026490D00		B1109490L00  φ1.9mm	MAT10903N00  P=1.6mm	礼服、连衣裙、大衣、运动上衣、内衣等的镶边缝制用	
94	2394	B1524491LBA		 1.5mm	B3026490L0A		B1109490L00  φ1.9mm	MAT10903N00  P=1.6mm	连衣裙、上衣、内衣、女服等的镶边缝制用 (针脚宽度1.5mm左段压脚)	
95	2395	B1524491LBB		 20mm 1.5mm	B3026490L0B		B1109490L00  φ1.9mm	MAT10903N00  P=1.6mm	连衣裙、上衣、内衣、女服等的镶边缝制用 (针脚宽度1.5mm左段压脚)	
96	2396	B1524491LBC		 25mm 1.5mm	B3026490L0B		B1109490L00  φ1.9mm	MAT10903N00  P=1.6mm	连衣裙、上衣、内衣、女服等的镶边缝制用 (针脚宽度1.5mm左段压脚)	

C/N	压脚(组件)		上送料压脚		针板		传送齿	注释
	品号	形状	品号	形状	品号	形状	品号 P=1.5mm	
97	2397	B1524491LBB  	B3026490LOC 	B1109490L00 	MAT10903N00 	强化上传送压脚的传送力。(1.5mm针脚宽度用左段压脚) B3026490LOB上传压脚倾斜→变成直角		
98	2398	B1524491MB0  	B3026491M00 	B1109450G0B 	B1613450G00 	连衣裙、女服、外套、裙子等下摆三卷用（针脚宽度1mm左台接压脚）		
99	2399	B1524491MBA  	B3026491M00 	B1109450G0B 	B1613450G00 	工作服上衣等袖口橡胶三卷用的台阶压脚（针脚宽度2mm左台阶压脚）		
100	2400	B1524491MBD  	B3026491M0D 	B1109450G0B 	B1613450G00 	连衣裙、女服、外套、裙子等下摆三卷用		
101	2401	B1524491MBF  	B3026491M0F 	B1109450G0B 	B1613450G00 	连衣裙、女服、外套、裙子等下摆三卷用		
102	2402	B1524491MBH  	B3026491M0H 	B1109450G0B 	B1613450G00 	M类型的压板为箱型，防止三卷部滑脱的类型 (针脚宽度1mm左段压脚)		

C/N	压脚(组件)		上送料压脚		针板		传送齿	注释	
	品号	形状	品号	形状	品号	形状	品号		
103	2403	B1524491NB0			B3026490N00				女服、罩衫、连衣裙、大衣、运动上衣等缝制滚边用
						$2.5 \times 1.7\text{mm}$			
104	2404	B1524491NB0			B3026490N00				女服、罩衫、连衣裙、大衣、运动上衣等缝制滚边用
						$2.5 \times 1.7\text{mm}$			
105	2405	B1524491PB0			B3026491P00				连衣裙、女服、裙子、工作服上衣等加缝拉链之用 进行加工，可以从针孔到端面mm
						$\phi 1.9\text{mm}$			
106	2406	B1524491PB0			B3026491P00				连衣裙、女服、裙子、运动服等加缝围裙拉链用
						$\phi 1.9\text{mm}$			
107	2407	B1524491PB0			B3026491P00				连衣裙、女服、裙子、运动服等加缝围裙拉链用 传送齿角度20度直进性提高的类型
						$P=1.9\text{mm}$			
108	2408	B1524491PB0			B3026491P00				PB类型传送齿反向型
						$P=1.9\text{mm}$			

C/N	压脚(组件)		上送料压脚		针板		传送齿	注释			
	品号	形状	品号	形状	品号	形状	品号				
109	2409	B1524491PB0			B3026491P00		B1109490P0D		B1613490P00		连衣裙、女服、裙子、运动服等加缝围裙拉链用
110	2410	B1524491PBE			B3026491P0E		B1109490P00		B1613490P00		JN类型的反向型，抑制布料抖动的类型
111	2411	B1524491PBF			B3026491P00		B1109490P00		B1613490P00		JA类型的反向型
112	2412	B1524491QB0			B3026490Q0B		B1109490E00		B1613490E00		为了抑制布料抖动，落针的全周由上传送压脚传送的类型
113	2413	B1524491QBA			B3026490Q0B		B1109490E00		B1613490E00		只按一侧的类型，对工作服上衣等安装拉链效果也不错
114	2414	B1524491SB0			B3026490S00		B1109490S00		B1613490S00A		具备刮入型和牵头型两种的中间特性的类型

C/N	压脚(组件)		上送料压脚		针板		传送齿	注释
	品号	形状	品号	形状	品号	形状	品号	
115	2415	B1524491SB0			B1109490S00	 φ1.4mm	B1613490S0A  P=1.5mm	S类型的传送齿距变大的类型，对厚物及有伸缩性的材料效果不错
116	2416	B1524491SB0			B1109490S00	 φ1.4mm	B1613490S00A  P=1.15mm	用于防止被褥织物材料、尼龙、塔夫绸、衬里等薄材料等的布疵 B3026490S00格上乌拉坦的类型
117	2417	B1524491SBC			B1109490S00	 φ1.4mm	B1613490S00A  P=1.15mm	女装、薄女服、罩衫等暗缝工序用S类型的落针容易看到的类型
118	2418	B1524491SB0			B1109450D0B	 2.5×1.7mm	B1613450E00  P=1.5mm	丝绒缝制专用类型 ※请与附加装置S135并用。
119	2419	B1524491WB0			B1109490W00	 φ1.6mm	B1613490W00  P=1.15mm	女性裙子腰带落疏缝用，从里侧落下的类型 ※请与附加装置Q049并用。
120	2420	B1524491WBA			B1109490W00	 φ1.6mm	B1613490W00  P=1.15mm	使落针接近INVEL的类型 ※请与附加装置Q049并用。